





US office:Fontana
UK office:Ipswich



USER'S MANUAL
Rain Barrel


## PLEASE READ INSTRUCTIONS CAREFULLY BEFORE FIRST USE

## To Operate the Bottom Drain



Attach any ordinary garden hose directly onto the spigot.





Zip the top all the way around and place Rain Barrel under your gutter's downspout to allow water to flow into barrel. Built-in mesh filter in top cover, filters out leaves and debris.




Open or close the spigot by turning the red thumb screw counter-clockwise to open and clockwise to close



Unzip the top cover for access to the water inside to fill a watering can or bucket.




Can be drained without using garden hose, just open the spigot.





valve and hose connector

**To Assemble Bottom Drain Spigot**Remove the rubber washer (B) and the plastic nut (A) from the spigot and insert the spigot into the hole (C) in the bottom of the Rain Barrel.




Reattach the rubber washer first and then the plastic nut from the inside of the Rain Barrel to secure the spigot in place.





## **To Assemble Top Overflow Valve** Remove the rubber washer (E) and the

Remove the rubber washer (E) and the plastic nut (F) from the overflow valve. Insert the valve into the hole in the top of the Rain Barrel (G) and replace the rubber washer and plastic nut from the inside of the Rain Barrel to secure.





The overflow valve works perfectly alone, but you can attach a hose or tube to direct the overflow.



## To Assemble the Rain Barrel Frame

Insert the four metal poles into the slot openings on the bottom of the Rain Barrel.



 $\frac{3}{4}$